



ANLY TIMER

AH3 MULTI-RANGE ANALOGUE TIMER



CHARACTERISTIC :

- Customized CMOS IC for low power consumption, high operation stability and extreme timing accuracy
 - Flush mount with Type Y-40 adapter and surface mount without adapter
 - 5 (NA, NB, NC, ND, NE) timing series available *
 - Each timing series has 4 time ranges, selectable via DIP switch *
 - 2 modes selectable via slide switch: Mode A (2C) for DPDT time-limiting output contacts and Mode B (1A1C) for SPDT instantaneous and time-limiting output contacts
 - UL, C-UL recognized and CE certified
- Note: "*" indicates applicable to AH3 multi-range series only

SPECIFICATION :


Operating voltage	DC(V): 12, 24 AC(V): 12, 24, 110, 220, 240
Allowable operating voltage range	85~110% of rated operating voltage
Rated frequency	50 / 60 Hz
Contact rating	250VAC 5A (resistive load)
Reset time	MAX 0.1S
Power consumption	Approx. 2VA
Life	Mechanical: 5,000,000 times Electrical: 100,000 times
Ambient temperature	-10 ~ +50°C
Ambient humidity	MAX 85%RH
Weight	Approx. 160g

TYPE SELECTION :


Model	Variable			Multi Range Variable		
Output contact	1C	2C	1A1C	Mode A / B		
Type	AH3-1	AH3-2	AH3-3	AH3-NA	AH3-NB	AH3-NC
Time range	1, 3, 6, 10, 30 or 60S 3, 6, 10, 30 or 60M, 3, 6, 10 or 24H			1S / 10S / 1M / 10M	3S / 30S / 3M / 30M	6S / 60S / 6M / 60M
Type				AH3-ND	AH3-NE	
Time range				1M / 10M / 1H / 10H	3M / 30M / 3H / 30H	

CONNECTION :


1C



2C, Mode A




1A1C, Mode B




TIMING CHART :


1C



2C, Mode A




1A1C, Mode B




DIMENSIONS : (mm)

N type(Surface Mounting): Using PF085A Socket & FH-3



Y type(Flush Mounting): Using Y-40 Frame & US-08 Socket or P3G-08 Socket



ANLY ELECTRONICS CO., LTD.

<http://www.anly.com.tw>

TAIWAN MAIN OFFICE : ANLY ELECTRONICS CO., LTD.

No.19, Lane 202, Fushou St., Shinjuang City, Taipei, Taiwan 242
TEL: +886-2-2996-3202 FAX: +886-2-2996-2017

MALAYSIA BRANCH : JUSTY ELECTRONICS (M) SDN, BHD.

No.1, Jalan 6/89B, Kawasan Perindustrian Trisegi, Batu 3 1/2 Off Jalan Sungei Besi, 57100 Kuala Lumpur, Malaysia
TEL: +60-3-7983-5758 FAX: +60-3-7981-5052

HONG KONG BRANCH : ANLY ELECTRONICS (HK) LTD.

Flat K, 13/F, Edward Mansion, 141 Prince Edward Road W., Kowloon, Hong Kong
TEL: +852-2397-2505 FAX: +852-2397-6080

SHANGHAI BRANCH : ANLY TECHNOLOGY (WUXI) CO., LTD.

Room 13G, No.831, Xinzha Rd., Jingan District, Shanghai, China 200041
TEL: +86-21-6218-3300 FAX: +86-21-6217-5911

NO. AH3-G-A